

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number  
WO 2004/113906 A1

(51) International Patent Classification?: G01N 29/24 (74) Agents: CALDERBANK, Roger et al.; Mewburn Ellis LLP, York House, 23 Kingsway, London Greater London WC2B 6HP (GB).

(21) International Application Number: PCT/GB2004/002648 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(22) International Filing Date: 18 June 2004 (18.06.2004) (82) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English (75) Inventors; and

(26) Publication Language: English (75) Inventors/Applicants (for US only): PAIGE, David [GB/GB]; 23 Wilmington Close, Kenton Bank Foot, Newcastle upon Tyne, Tyne and Wear NE3 2SF (GB). MERCEL, Robert, Andrew [GB/GB]; 11 Falstone Crescent, Ashington, Northumberland, Tyne and Wear NE63 0TY (GB). SOWERBY, Ian [GB/GB]; 8 Kingsway, North Shields, Northumberland, Tyne and Wear NE30 2LY (GB).

*[Continued on next page]*

(54) Title: ELECTROMAGNETIC ACOUSTIC TRANSDUCER



WO 2004/113906 A1

(57) **Abstract:** An electromagnetic acoustic transducer (12, 24) has one or a plurality of magnets for applying a DC magnetic field to a material (4, 25) under test, and an electrical coil (2, 23) supplied by an alternating current source for providing an AC magnetic flux within the material under test. A wear plate (16, 26) engages with an slides along the surface of the material under test. The wear plate (16, 26) is of electrically conductive ferromagnetic material and has apertures (17, 31) therein. Thus, both the DC field and the ACT flux can penetrate the material under test and create ultrasonic vibration of that material.